
Greasy smooth coat ULIROC



Product attributes:

Packaging: 0,5 L, 5 L

Product codes:

Reference: P5029/XX

EAN13: -

UPC: -

Product features:

Packing: 5 L

Packing: 0.5L

Use precaution: Drying after 6 hours in thin layer, sanding after 12 hours with dry abrasive and recoverable after 24h.

Hue: White

Product short description:

Greasy and thin coating with high hardness and neat laquer finish.

Makes the one-layer-finish easy, can be applied as well on exterior as interior surfaces.

For a perfectly smooth finish we recommend to apply first ULIROC pitch.

This greasy coating allows you to lacquer your surfaces directly if the base is solid, clean and dry.

Ambiant air : 20°C, humidity : 60%

Product description:

Product gallery:

ULIROC
Ciment Portland avec addition de fibres ultra-fines, sans plomb, CEM II/A-42,5R, conforme aux normes EN 12596 et EN 12597, fabriqué en France.
Ciment Portland avec addition de fibres ultra-fines, sans plomb, CEM II/A-42,5R, conforme aux normes EN 12596 et EN 12597, fabriqué en France.
Ciment Portland avec addition de fibres ultra-fines, sans plomb, CEM II/A-42,5R, conforme aux normes EN 12596 et EN 12597, fabriqué en France.

COMUS
ULIROC
CIMENT GRAS DE
BATTAGE TRÈS DUR
Ciment Portland avec addition
de fibres ultra-fines
sans plomb

OPINIENS ET SÉCURITÉ

COMUS est certifié par le Bureau Veritas

COMUS est certifié par le Bureau Veritas